Juni Khyat ISSN: 2278-4632 (UGC Care Group I Listed Journal) Vol-13, Issue-04, No.06, April : 2023 SECURITY AND COMMUNICATION NEW ROUTING FOR CONTRASTING WIRELESS SENSOR NETWORKS

¹ DR. GURU KESAVA DAS. GOPISETTY¹ Professor & HOD in CSE Department Universal College of Engineering & Technology

 ²P. JAGADEESH BABU²Assistant professor Eluru College of Engineering and Technology
³DR CH RAMESH BABU ³ Associate Professor, Department of IT Matrusri Engineering College
⁴M NARENDRA NADH REDDY⁴Assistant professor at Universal College of Engineering & Technology

ABSTRACT: In latest systems middle hop nodes which works for each and every data transmission consumes maximum energy which repeatedly affects the life time of the wireless sensor network. Power-efficient Energy-Aware routing protocol for wireless sensor networks is proposed that saves the energy by efficiently selecting the energy efficient path in the routing process. We propose use of new sensor network is query operators are assigned to sparsely deploy resource-new nodes within a dense network of low power sensor nodes. Energy proficiency is a standout many the most critical debugs in mobility based wireless sensor network. Routing procedures for WSNs are responsible for selecting and maintaining the routes in the network and security reliable and effective communication in inadequate periods. Proposed new sub optimal paths occasionally to increase the lifetime of the network limitations of current method is propose a new MAC layer protocol called Convergent MAC (CMAC) that supports low latency and high throughput as well as low duty cycle operation. The proposed EAUM-WCH protocol is new efficient in balancing the stability and consumption of energy in the network and improves the lifetime wireless sensor network. In order to increase the energy efficiency further transmission power of the nodes is also adjusted based on the location of their neighbor. To the best of our knowledge, this is the first attempt to build an energy aware routing infrastructure to enable in-network processing of spatial-temporal queries.

Index Terms: CMAC, MANET, MAC, Location aware, scalability, hierarchical, Clustering, Review, Cluster-Head, Energy Effectiveness, Information gathering, Security. Delivery Ratio, Energy Consumption, end-to-end delay

INTRODUCTION

Wireless sensor networks (WSNs) are arranging much attention all over the globe due to its sensing capability and stability. The Micro Electro Mechanical System is introduced low powered compact sensor nodes [1]. The sensor nodes perform desired applications process the measured data and transmit it to a base station, commonly referred to as the sink node over a wireless channel [2]. At the node level data communication is the dominant component of energy consumption, and protocol design for sensor networks is geared towards reducing data traffic in the network [3]. A large number of cheap sensor nodes and transmit data and some powerful nodes Query Processor (QP) nodes execute query operators to combine and process data arriving from multiple target regions [4]. While sensing and broadcasting information energy is devoured in sensor node. Information broadcasting throughout medium is the most energy consuming task [5]. Latest wireless communication technologies and the manufacture of inexpensive wireless devices have led to the introduction of low-power wireless sensor networks [6]. Mobile Ad-hoc networks (MANET) are self-configuring and self-organizing multi hop wireless networks structure changes dynamically [7]. To achieve high quality of service the energy and lifetime improvement in wireless sensor network is concentrated core motivation for developing any transmission prototype. Various kinds of design patterns are developed according to the concept of energy conservation in WSN [8].

Juni Khyat (UGC Care Group I Listed Journal)



Fig. 1– A Simple node architecture

RELATED WORK

There are four main categories of routing protocols in WSN are data-centric, hierarchical, locationbased and multipath: In data-centric routing, the sink sends queries to certain regions and waits for data from the sensors located in the selected regions [9]. We propose that the cost and delay take in transmitting raw data to a remote server for offline result computation is eliminated by processing data from spatially distributed regions within the network [10]. Received-Signal Strength-Indicator (RSSI) the information broadcasting consume greatest power is used to resolve signal quality which can shift because of multipath [11]. In this context, researchers have proposed numerous routing protocols to improve performance demands new applications in the network layer of wireless sensor networks protocol stack [12]. The goal of Wireless sensor network long life time and high reliability with maximum coverage Routing method is the most important issue for networks where resources are limited. LEACH is one of the first hierarchical routing methods for sensor networks [13].

SYSTEM MODEL

We present the proposed communication system model spatio temporal monitoring applications in the bird's eye view of a sensor field with data streams emerging from multiple target regions and being merged at intermediate nodes in the network into a single output stream directed towards the sink [14]. We assume that a user query specified in a declarative language like SQL has been converted to a query tree is using query optimization techniques based on power conservation [15]. This path is selected by the proposed protocol for routing from source to sink. Sink represents the command node. A command node is stationary [16]. The proposed protocol collects routes is minimum residual energy of nodes relatively large and have the least hop-count, and then determines a proper route number of consumes the minimum network energy compared to any other routes [17].



Figure2: Block Diagram of system model

PROPOSED METHODS

Proposed a MAC layer protocol called Convergent MAC (CMAC) to supports low latency and high throughput as well as low duty cycle operation CMAC is three main components [18]. The battery powered sensors is limited energy and so protocols should minimize their data communication and computation. One of the routing protocol is proposed early on, which provides some QoS, is the

Pag | 152 DOI10.36893.JK.2023.V13I04N16.00151-00156

Juni Khyat (UGC Care Group I Listed Journal)

ISSN: 2278-4632

Vol-13, Issue-04, No.06, April : 2023

Sequential Assignment Routing (SAR) protocol [19]. It modify the entire network to regulate to the arbitrary adaptability of sensor nodes. It is a dynamic and energy capable method which improves the time span of network throughput level and energy effectiveness [20].



Fig. 3 - Proposed architecture for WSNs

METHODOLOGY

CMAC: Proposed a MAC layer protocol is Convergent MAC (CMAC) that supports low latency and high throughput as well as low duty cycle operation. Aggressive RTS equipped with double channel check for channel assessment any cast to quickly discover forwarder, and convergent packet forwarding to reduce the any cast overhead [21]. CMAC uses unsynchronized wake-up scheduling with a pre-defined idle duty cycle this wake-up scheduling scheme the duration between successive wake-ups is fixed according to the duty cycle and active period. However to make the following mechanisms work at expected performance we evenly randomize the wake-up time of each node for the first times it goes back to sleep after receiving a packet [22].



Figure 4. Basic Architecture of Wireless Sensor Network

Cluster Building

To perform the operation of building a cluster, the proposed protocol determines links by means of: **Step 1:** Input link brsides,

Step 2: Stability value of the each and every link calculation,

Step 3: Linked nodes energy sufficient values,

Step4: The linked nodes distance calculation.

Links weight is the main criteria to determine the nodes weight. Then, it is followed by the election of cluster head node to weights and also elects the cluster child of the cluster [23].

Cluster Head Rotation

Pag | 153 DOI10.36893.JK.2023.V13I04N16.00151-00156

Copyright@2023 Author

Juni Khyat

(UGC Care Group I Listed Journal)

ISSN: 2278-4632 Vol-13, Issue-04, No.06, April : 2023

Cluster head node consumed energy is comparatively higher to compare the cluster child nodes because it receives all the information from the cluster child nodes is a forwarder in the current cluster is handle the operation of backbone network information forwarding process. The event based CH rotation method is proposed with the help of the following packet definitions [24].

Step 1: CH rotation node packet, including CH address.

Step 2: CH rotation response data packet.

Step 3: CH appointment packet, including CH address appointment.

Step 4: CH lost contact data, when cluster nodes been unsuccessful to connect in the particular time period then the data packets are multicast to other cluster nodes.

Quality of Service Routing Protocols for WSN

Quality of Service (QoS) requirements like delay, reliability and fault tolerance are as important in routing in WSNs as energy efficiency. Routing protocols that support QoS with energy efficiency

Step1: Sequential Assignment Routing (SAR) protocol one of the routing protocols that was proposed starting on, which provides some QoS, is the Sequential Assignment Routing (SAR) protocol.

Step2: SPEED QoS routing Protocol SPEED [6] is designed to support soft real-time communication service by maintaining the desired delivery speed across the network so that the end-to-end delay is minimized.

Step3: Energy-Aware QoS Routing Protocol Real-time traffic is generated by imaging sensors in this QoS energy aware routing protocol this protocol finds the least cost and energy efficient path and the link cost is a function that captures the nodes energy reserve, transmission energy, error rate and some communication parameters [25].

Step4: Message-Initiated Constrained-Based Routing A Message-Initiated Constrained-Based Routing (MCBR) mechanism is proposed in [25]. MCBR is composed of explicit specifications of constraint-based destinations, route constraints and QoS requirements for messages, and a set of QoS aware meta-strategies.



Figure 5: Network Establishment Routing Path

EXPERIMENT RESULT

NS2 simulation results are obtained from experiment repeats for consistency, comparison of different architectures to the proposed WSN protocol. It was observed that the proposed model had a much better performance reliability compared to other protocols. In our simulations, we evaluate a CMAC variant using a staggered scheduling similar to DMAC after convergence. When the transmitter intends to converge from any cast to uncast, it synchronizes its schedule with the receiver. EQSR uses the multipath paradigm together with a Forward Error Correction (FEC) technique to recover from node failures without invoking network wide flooding for path-discovery.

Juni Khyat (UGC Care Group I Listed Journal)



Fig No. 6. Simulation Time Vs Number Of Detected Node

CONCLUSION AND FUTRUE ENHANCEMENT

Motivated by the limitations of current model is propose a new MAC layer protocol called Convergent MAC (CMAC) that supports low latency and high throughput as well as low duty cycle operation. The protocol is updating dynamically by a constrained optimization problem. This taxonomy includes flat hierarchical QoS and location based routings and numerous other it discusses several multi-path routing model used to modify network metrics such as lifetime and latency. The compared energy proficient clustered routing methodology depends on CH selection. Many research people are working in this area to improve the results of the network further with more energy efficient models. Proposed Energy efficient routing protocol is wireless sensor network invokes the residual energy and hop count as parameters. In the future scope new routing algorithms are handling the overhead of mobility and network changes in such energy constrained environment. Location based energy-aware reliable routing by implementing clustering with security such as secured routing for packet transmission is implemented and improve quality of service by adding Qos parameters.

REFERENCES

[1] S. Tanwar, N. Kumar, and J. J. Rodrigues, "A systematic review on heterogeneous routing protocols for wireless sensor network," Journal of network and computer applications, vol. 53, pp. 39-56, 2015

[2] Zijian Wang, Eyuphan Bulut, and Boleslaw K. Szymanski, —Energy Efficient Collision Aware Multipath Routing for Wireless Sensor Networksl, International Conference on Communication June 14-18, 2009.

[3] An Energy-Aware Routing Protocol in Wireless Sensor Networks Ming Liu 1, Jiannong Cao 2, Guihai Chen 3 and Xiaomin Wang Sensors 2009.

[4] Lu Su, Changlei Liu, Hui Songand Guohong Cao —Routing in Intermittently Connected Sensor Networks 2008 IEEE.

[5] K. Akkaya, and M. Younis, "A Survey on Routing Protocols for Wireless Sensor Networks", Elsevier Ad Hoc Network Journal, vol. 3, no. 3, pp 325-349, 2005.

[6] Q. Jiang and D. Manivannan, —Routing protocols for sensor networks, Proceedings of CCNC 2004, pp.93-98, Jan. 2004.

[7] A.P. Subramanian, A.J. Anto, J. Vasudevan, and P. Narayanasamy, —Multipath power sensitive routing protocol for mobile ad hoc networks^{II}, Proc. Conf. Wireless on Demand Network Systems, 2004, LNCS 2928, 2004, pp. 171-183.

[8] Charles E. Perkins, "Ad hoc On-demand Distance Vector (AODV) Routing.", RFC 3561, IETF MANET Working Group, July 2003.

[9] F. Ye et al., —A Two-tier Data Dissemination Model for Large-scale Wireless Sensor Networks, in the Proceedings of Mobicom'02, Atlanta, GA, Septmeber, 2002.

[10] M. Chu, H. Haussecker, and F. Zhao, "Scalable Information-Driven Sensor Querying and Routing for ad hoc Heterogeneous Sensor Networks," The International.

Pag | 155 DOI10.36893.JK.2023.V13I04N16.00151-00156

Juni Khyat

(UGC Care Group I Listed Journal)

Vol-13, Issue-04, No.06, April : 2023

ISSN: 2278-4632

[11] N. Jain, "Energy Aware and Adaptive Routing Protocols for Wireless Sensor Networks," Ph.D. Thesis, Computer Science, University of Cincinnati, Summer 2004.

[12] Y. Yu, R. Govindan, and D. Estrin, "Geographical and Energy Aware Routing: A Recursive Data Dissemination Protocol for Wireless Sensor Networks," UCLA Computer Science Department Technical Report UCLA/CSD-TR-01-0023, May 2001.

[13] B. Karp and H.T. Kung, —GPSR: Greedy perimeter stateless routing for wireless networks", proceedings ACM MobiCom '00, Boston, MA, Aug .2000, pp. 243-254.

[14] C. Intanagonwiwat, R. Govindan, D. Estrin, J.Heidemann, and F. Silva,"Directed diffusion for wireless sensor networking",IEEE/ACM Transactions on Networking, vol. 11.,no. 1, Feb. 2003.

[15] C.Intanagonwiwat, R.Govindan, and D.Estrin,"Directed diffusion: A scalable and robust communication paradigm for sensor networks", Proceedings ACM MobiCom'00, Boston, MA, Aug.2000.

[16] I.F. Akyildiz, W.Su, Y. Sankarasubramaniam, and E. Cayirci, —Wireless sensor networks: a surveyl, computer networks (Elsevier) Journal, Vol.38, no.4, Mar.2002, pp. 393-422.

[17] J. Kulik, W. Heinzelman, and H. Balakrishnan, —Negotiation - based protocols for disseminating information in wireless sensor networks", Wireless Networks, vol. 8, no. 2/3, Mar.-May 2002.

[18] Jamal Al-Karaki, and Ahmed E.Kamal, —Routing Technique in Wireless Sensor Networks: A Surveyl, IEEE Communications Magazine, vol 11, no.6, Dec.2004, pp 6-28.

[19] K.Akkaya and M. Younis, —An Energy-Aware QoS Routing Protocol for Wireless Sensor Networks, in the Proceedings of the IEEE Workshop on Mobile and Wireless Networks(MNV2003), Providence, Rhode Island, May2003.

[20] Kemal Akkaya and Mohamed Younis, —A Survey on Routing Protocols for Wireless Sensor Networks, Ad hoc Networks, vol. 3, no. 3, May 2005.

[21] Heinzelman W. Chandrakasan A. Balakrishnan H.,"energy-Efficient Communication Protocol for Wireless Microsensor Network"s, Proceedings of the 33rd Hawaii International Conference on System Sciences, January 2000.

[22] Meenakshi Sharma, Kalpana Sharma, "An Energy Efficient Extended LEACH (EEE LEACH)", International Conference on Communication Systems and Network Technologies, 2012

[23] Arezoo Yektaparast, Fatemeh-Hoda Nabavi, Adel Sarmast,"An Improvement on LEACH Protocol(Cell-LEACH), Advanced Communication Technology (ICACT)", 2012 14th International Conference on, Feb. 2012.

[24] Scow Guther, CertCo, "Wireless Relay Networks", IEEE Network, November 1997.

[25] Ke Liu, Nael Abu-Ghazaleh, "Reliable Energy Aware Routing in Wireless Sensor Networks", Proceedings of the Second IEEE Workshop on Dependability and Security in Sensor Networks and Systems, 2006.